Standard M2 Desktop Booklet Maker

Instruction Manual



Call Us at 1-800-944-4573

OPERATIONS MANUAL

Standard Nagel M2 Bookletmaker

Read this manual, and thoroughly familiarize yourself with its contents before operating or servicing this equipment.








fig. 01

CONTENTS

- 1. SETUP
- 2. LOADING OF STAPLE MAGAZINE
- 3. ADJUSTMENTS
 - 3.1 PAPER WIDTH
 - 3.2 PAPER LENGTH
 - 3.3 POSITION OF STAPLING HEADS
- 4. BOOKLETMAKING OR FOLDING
- 5. TROUBLESHOOTING
- 6. MAINTENANCE
- 7. SECURITY
- 8. TECHNICAL DATA

Congratulations for choosing to purchase the BOOKLETMAKER FOLDNAK M2.

It makes fast and easy works of producing impressing looking booklets. Even small quantities become efficient to produce because adjustment requirements are minimal.





COMPONENTS DELIVERED

BOOKLETMAKER FOLDNAK M2 with two stapling heads, bag with two knurled screws (1), 5.000 NAGEL-Staples 26/6, instructions manual.

1. SETUP

Screw in the two knurled screws (1). Plug in the power cord.

2. LOADING OF STAPLE MAGAZINE

- Pull staple pusher (12) back until it locks on by itself
- Open magazine cover (13)
- Load staples
- Close magazine cover (13)
- Push staple pusher (12) gently down to unlock it and guide it towards the machine's front side. Do not let the staple pusher snap forward because this would smash the stick of staples.

You can use either of the three original NAGEL-Staple types 26/6 or Ri 26/6. We recommend that you use the staple types as shown below:

Staple Type:	Loop Staple	Flat Staple
	Ri 26/6	26/6
(Use only NAGEL staples as other staples may damage the stapling head or lead to bad results.)	گ	
Booklets (2-15 sheets)	X	X





3. ADJUSTMENTS

3.1 PAPER WIDTH

- Position the left side guide (10) according to the paper format required using the scale (2) and fix it with the knurled screw (1)
- Insert paper squaring it up parallel to the left guide (10)
- Shift the right side guide (11) closely to the inserted paper and fix it, leaving 1mm of air. <u>Important</u>: The side guides (10, 11) must not catch on the movement of the sheets.

3.2 PAPER LENGTH

- Open cover (5)
- Adjust and fix the back stop (14) according to your paper format using the scale
- Close cover (5)

Check the adjustments 3.1 and 3.2 with a test run and readjust if necessary. 3.3 POSITION OF STAPLING HEADS

The BOOKLETMAKER FOLDNAK M2 is able to use four stapling positions with up to four stapling heads (USA: 5 stapling positions with up to three stapling heads). DIN-distances between the stapling heads are 50x80x50mm (USA: 2 1/8" on center).

- Unlock the latch (15)
- Take out stapling head, put it into a new position and lock the latch (15). The driver blade's (16) hole needs to be hinged onto the pin (17), and the mark "26" on the driver blade must show towards the rear side of the machine.





4. BOOKLETMAKING OR FOLDING

- Adjust guides (10, 11, 14) to paper format
- Insert paper making sure the sheets are squared up correctly
- Push button "START" (6)

The stacker (4) can be used to stack a couple of booklets. If you only want to fold paper without stapling then just remove the staples from the stapling heads.





5. TROUBLESHOOTING

Machine is switched on, but the light inside the ON/OFF-Selector (7) is not on

The power cord is plugged in improperly:	: Push power cord thoroughly into power	
	outlet.	
Circuit braker has been activated:	Push circuit braker button in again. It is	
	located at the machine's rear, beneath the	
	power cord outlet.	
Internal problem:	Contact your dealer.	

Button "START" (6) is being pushed, but machine does not work

Cover (5) is open:	Close cover.
Staple jam inside staple channel:	Take off stapling head, remove both
	screws of front plate (18), take off front
	plate. Remove jammed staple, clean staple
	channel and reassemble.
Jam of the moving parts because too	Push button "RESET" (9) for a few sec-
much paper has been inserted:	onds. The machine then runs backwards,
	enabling the operator to pull out jammed
	paper.
Circuit braker has been activated:	Push circuit braker button in again. It is
	located at the machine's rear, beneath the
	power cord outlet.
Internal problem:	Contact your dealer.





Machine does not staple although the staple magazine is filled

Driver blade (16) is not hinged onto pin	Hinge hole of the driver blade (16) onto
(17):	pin (17).
Driver blade (16) is missing:	Put in a driver blade. The mark "26" must
	show towards the rear side of the ma-
	chine.
Staple jam inside staple magazine:	Use original NAGEL-Staples and make
	sure to only use types 26/6 or Ri 26/6.
Staple pusher (12) does not push staples:	Push staple pusher gently down to unlock
	and guide it towards the staples.
Staple jam inside staple channel:	Take off stapling head, remove both
	screws of front plate (18), take off front
	plate. Remove jammed staple, clean staple
	channel and reassemble. Use only original
	NAGEL-Staples and make sure to only
	use types 26/6 or Ri 26/6.

Frequent misstapling or two staples in one position

Insufficient staple quality:	Use original NAGEL-Staples.	
Incorrect staple type:	Use original NAGEL-Staples, types 26/6	
	or Ri 26/6 only. See chapter 2.	
Driver blade (16) has been put in the	Put in the driver blade with the mark "26"	
wrong way round:	showing towards the rear side of the ma-	
	chine.	
Residues inside staple channel:	Take off stapling head, remove both	
	screws of front plate (18), take off front	
	plate. Clean staple channel and reassemble	
	the stapling head.	
Driver blade (16) is scratched or bent:	Put in a new driver blade.	
Button "START" (6) is being pushed	Remove jammed staples from the anvils	
without paper inside the machine:	and fire only with paper being inserted.	





Booklet is stapled correctly but incorrectly ejected

Reduced stickiness of fold rollers because	Clean fold rollers.
of dirt:	
Too many sheets have been inserted:	Do not insert more than 15 sheets. See
	chapter 9.

Booklets are being stapled or folded incorrectly

The side guides (10, 11) or the back stop	Fix the locking screws of the side guides
(14) are fixed improperly and move	and back stop properly.
around:	
The side guides (10, 11) are too far apart	Shift side guides more closely together.
from each other, allowing unparallel inser-	See chapter 3.1.
tion of paper:	
The side guides (10, 11) are adjusted too	Shift side guides farther apart. See chapter
tightly, causing larger paper formats to	3.1.
curl during folding which leads to incor-	
rect stapling.	
Incorrect adjustment of back stop (14):	Adjust back stop more precisely, so that
	the machine folds in the center of the
	sheets.
Paper is not squared up correctly:	Square up paper correctly before firing.





6. MAINTENANCE

Replace scratched or bent driver blades (16). Clean the machine only with a soft and humid tissue without chemical substances. Clean the folding rollers using a substance that does not dissolve rubber.

7. SECURITY

- The machine must only be used for the stapling and folding of paper.
- Connect machine only to an earthed power outlet. Switch off after use.
- Make sure that the power requirement indicated at the machine's rear side is the same being provided on your premises before connecting the power cord. Check function of safety shut off regularly: The machine must not run with cover (5) opened.
- Clean and service the machine only with the power cord disconnected.
- Place on an even support and never in a humid surrounding, avoid direct sunlight immission.
- Never put mugs, glasses or bottles onto the machine.
- If you notice smoke, heat, excessive noises or any unusual performance, disconnect the power cord immediately and call your dealer.





8. TECHNICAL DATA

Input paper sizes for booklets DIN A5 $(5\frac{1}{2}x8\frac{1}{2}")$ - A3 (11x17", SRA3)

Maximum booklet size 60 pages or 15 sheets 80g-paper 2, upgradeable to 4 (USA: max. 3)

Staple magazine 210 staples/stapling head

Staples/Loop Staples NAGEL 26/6 (6mm leg length)

NAGEL Ri 26/6 (6mm leg length, loop) NAGEL 26/8S (8mm leg length, steel) User dependent up to 500 booklets/h

Cycle speed User dependent up to 500 booklets/h Power requirements 230V AC 50Hz, 100W / 110V AC 60Hz,

100W

Weight (shipping weight) 39kg/86lbs. (41,5kg/91,5lbs.) Dimensions (height x width x length) 290mm/11½" x 490mm/19 $^{1}/_{3}$ " x

510mm/20"

Shipping dimensions (height x width x length) $420\text{mm}/16^1/_{3^{"}} \text{ x }680\text{mm}/26^2/_{3^{"}} \text{ x}$

24"

Accessories Stand on Casters

Additional stapling heads Original NAGEL-Staples

Manufacturer ERNST NAGEL GMBH, Breitwiesen-

straße 21

D-70565 Stuttgart, Germany







