MBM Destroyit 4108 Level P-2 High Capacity Strip-Cut Paper Shredder - DSH0345L

Product Spec Sheet



Call Us at 1-800-944-4573

DESTROYIT® 4108

Wide feed table and powered conveyor for fast, efficient feeding. Equipped with an automatic oiling system and Easy Switch.

75-95
1/4 x 2 inches cross-cut (6 x 50 mm)
65-82

*Certified using 8.5" x 11" 20 lb. bond and recommended power supply.

2 x 15 Cross-cut model available by special order only



High shred speed for efficient shredding. EASY-SWITCH – intelligent multifunction control element indicating the operational status of the shredder with varying color codes and back-lit symbols. Electronic control prevents overfeeding: automatic reverse and refeeding in case of paper jams. Main switch and emergency cut-off switch. Robust shredding heads with special hardened cutting shafts made of high-quality steel, resistant against soft metal objects. Automatic oil injection on the cutting shafts during shredding operation for constantly high shred performance. Oil droplet icon will illuminate when more oil is needed. Automatic stand-by after 30 minutes. Powerful three phase motors. Thermal motor protection. Large shred compartment with door on the rear of the machine. Plastic bag suspension with pull-out mechanism on wheels for easy removal of the full bag. High volume bag for the shredded material. Automatic cut-off when shred bag is full or the door is open. Mobile on casters. Convenient transportation width of 27 1/8" (without side tables).

Specifications

•	
Shred volume, gallons	79
Feed opening, inches	16 1/8
Electrical requirements, volts	220, 3 phase
Maximum horsepower	10 (sc), 8 (cc)
Product Dimensions (D x W x H), inches	67 x 48.75 x 56.75
Product weight, pounds	787

MyBinding.com 5500 NE Moore Court Hillsboro, OR 97124 Toll Free: 1-800-944-4573

Local: 503-640-5920











DESTROYIT® 4108

Features



EASY-SWITCH

Ease of operation: intelligent multifunction switch with integrated optical signals indicating the operational status.



ELECTRONIC OIL INJECTION

The automatic oil injection system lubricates the cutting shafts when shredding and guarantees a constantly high shred performance.



PULL-OUT BAG SUSPENSION

Pull-out mechanism on wheels for easy removal of the full shred bag at the rear of the machine.



CONVEYOR BELT

The conveyor belt system guarantees a high work speed without creating paper jams. Also crumpled paper can be fed into the shredding head without problems.



ILLUMINATION OF THE WORKING AREA

The feeding area and the conveyor belt are illuminated by LEDs.







*High Capacity models have a 1 year limited warranty.

MyBinding.com 5500 NE Moore Court Hillsboro, OR 97124 Toll Free: 1-800-944-4573

Local: 503-640-5920







WWW.IDEAL-MBM.COM TEL: 800-387-2528





