

MBM Destroyit Degausser and Hard Drive Punch

Product Spec Sheet



Provided by

MyBinding.com
When Image Matters.

Call Us at 1-800-944-4573

DESTROYIT® DEGAUSSER / HDP

DEGAUSSER / HARD DRIVE PUNCH. Magnetically degausses hard drives from PCs, laptops, notebooks, printers, copiers, and PDAs, then punches a hole through the drive, destroying it irreparably. A slider mechanism drops the degaussed and punched drive into the enclosed bin to await proper disposal.

Security level H-3 (HDP unit)

Hard drive sizes, inches:	2 1/2 or 3 1/2
Erasing area (H x W x D), inches:	1 1/2 x 4 1/4 x 6
Degaussing cycle, seconds:	60
Degaussing system:	capacitive discharge
Degausser magnetic field:	8,700 Oe / .87 Tesla
Punching cycle, seconds:	15



Comprehensive SPS safety package (HDP unit): Easy Switch control element uses illuminated color codes and symbols to indicate operational status and functions as an emergency stop switch; electronically controlled, transparent safety shield in the feed opening; automatic stop after punching; automatic power cut-off when cabinet is opened or collection bin is full; double protection against overheating.

HDP unit: Punches a hole completely through the hard drive, making it unreadable. Suitable for 2 1/2 and 3 1/2 inch drives (single feed). Handy slide lever for easy selection of hard drive size. Adjustable feed chute made of high quality steel. LEDs illuminate feed chute during punching process. Punching die made of hardened, nickel-plated steel. Automatic reverse on punching die prevents jams. Slider mechanism for unloading punching compartment—destroyed drives drop into a sturdy collection bin to await proper disposal. Quiet and powerful single phase motor rated for continuous operation. Sturdy Twin Drive System with fully enclosed gear box housing.

Degausser unit: Erases hard drives (laptop, desktop, and network up to 1 1/2 inches high) and high coercivity tape media, including all formats of LTO, Super DLT I and II, AIT, 3590 Series, 8 mm and more. Fast, 60 second cycle time. High field strength and encompassing magnetic field ensure data is completely erased and non-recoverable, regardless of operating system or interface. Digital status indicator and field strength verification. No moving parts allow for extremely quiet operation. Rated for continuous operation (no cooling necessary).

High quality wooden cabinet mounted on casters. Anti-static collection bin made of impact-resistant plastic. 1 year warranty on all parts, excluding wearables.

MyBinding.com
5500 NE Moore Court
Hillsboro, OR 97124
Toll Free: 1-800-944-4573
Local: 503-640-5920

DESTROYIT® DEGAUSSER / HDP

Step-by-step operation



STEP 1

Drop a used hard drive into the slide-out drawer on the degausser unit. Most drives up to 1 1/2 inches are acceptable.



STEP 2

Close the drawer and the degaussing process automatically begins. In less than a minute, the drive is completely erased and may be removed.



STEP 3

Remove the drive from the degausser unit and place it in the HDP feed chute. Hit the start button and a hardened steel die is driven completely through the drive.



STEP 4

Use the slider lever to drop the destroyed drive into the sturdy collection bin to await proper disposal.

Specifications

Collection bin volume	weight sensor ¹
Electrical requirements, volts	115
Maximum horsepower (HDP)	1
Dimensions (D x W x H), inches	18 1/2 x 19 1/2 x 33 1/2
Shipping weight, pounds	247

¹automatic cut-off when collection bin is full



Above logos do not apply to degausser unit.



MyBinding.com
5500 NE Moore Court
Hillsboro, OR 97124
Toll Free: 1-800-944-4573
Local: 503-640-5920

HDP unit is GS / CE certified and UL listed.
Degausser unit is CE certified only.



All technical data is approximate and subject to change. © MBM Corporation, 3/2014.