

***Duralam Integra 27"***  
***Hot Roll Laminator -***  
***EGML2700***

Product Spec Sheet



*Provided by*

**MyBinding.com**

*When Image Matters.*

Call Us at 1-800-944-4573

# DURALAM™ INTEGRA

## EGML2700



The all-new Duralam™ Integra desktop laminator was designed by laminator technicians from across North America.

### Special Features

**TRUE VARIABLE SPEED-** allows the operator to process big sheet work at high speed, yet slow the speed as required to place small or very small workpieces on the infeed without wasting laminating film. Set the speed to suit the need pace, avoid waste and SAVE!

**SIMPLICITY OF CONTROLS-** By design, the control panel of the Duralam™ Integra is simple and user friendly, reducing problems due to operator error. Users can be easily trained how to run the Duralam™ Integra.

**SAFETY MECHANISIMS THAT WORK-** The chance of an operator getting burned by this laminator is virtually zero. Cut out the exorbitant cost and poor quality cold laminating.

**SIMPLEST LAMINATOR TO LOAD-** Using collar mounts, you can load both rolls in under five minutes-easily.

**QUICKEST WARM UP TIME-** Our technicians think 15 - 20 minute warmup times are a terrible waste of time and money. Warmup time for the Duralam™ Integra is only six minutes.

**AUTO SHUT OFF-** Default setting put the laminator in standby mode after one hour, and can also be set by a technician for 3 hour standby or bypass. Standby mode allows a return to full heat in 5 minutes.

# DURALAM™ INTEGRA

## EGML2700

### Additional Features Include:

**ENVIROMENTALLY FRIENDLY FILM CORES-** Just toss them in the recycle bin.

**SAFETY BACK CUTTER-** Quickly and efficiently trims your workpieces without any nasty finger cuts.

**FULL 27" WIDTH-** 27" film will easily and quickly mount on the Duralam™ Integra. Many other machines make it very difficult to mount the wide 27" roll, but not the Duralam™ Integra. It also easily accepts 4", 12", 18", and 25" film on a 1" core.

**INFINITELY VARIABLE HEAT-** allows your prime operator to set the heat to optimum when changing to a different film type.

**PROVEN INFRARED HEAT UNITS-** Amazingly simple but effective design resulting in a true increase in the life of both the heat unites and the heat rollers.

**13' LONG CORD AND PLUG-** Our way to protect you from the dangers of extension cords, and liability for insurance increases or OSHA penalties. Excellent for flexibility and ease of use.

**SERVICEABILITY-** Besides being a service technician's dream, the Duralam™ Integra is built for a minimum 20 year useful life.

### Specifications

Max Laminating Width	27 Inches
Max Film Thickness	1.2 mil - 5.0 mil
Supply Roll Core Size	1 Inch
Heating System	Infrared Heater/ Hot Silicone Roller
Lamination Type	2 Sided Thermal
Reverse Feature	Yes
Temperature Control	Variable up to 300°F
Speed Control	Variable up to 1-5'/ Minute
Preheat Time	6 Minutes
Rear Exit Cutter	Yes
Motor	DC Geared
Power Requirement	AC 120V/ 60Hz
Power Consumption	1440W/ 12A
Dimensions	18.5" L x 36" W x 12" H
Weight	80 lbs.
Warranty	1 Year