# Fellowes Powershred 465Ms Micro-Cut Paper Shredder

## **Instruction Manual**



Call Us at 1-800-944-4573



## **POWERSHRED**<sup>®</sup> 465Ms THE WORLD'S **TOUGHEST** SHREDDERS<sup>®</sup>



## **POWERSHRED**<sup>®</sup> 465Ms THE WORLD'S **TOUGHEST** SHREDDERS<sup>™</sup>

## LIMITED PRODUCT WARRANTY / GARANTÍA LIMITADA DEL PRODUCTO/ GARANTIE LIMITÉE DU PRODUIT

Limited Warranty: Fellowes, Inc. ("Fellowes") warrants the parts of the machine to be free of defects in where the shredder is initially sold by an authorized reseller. ANY IMPLIED WARRANTY, INCLUDING THAT material and workmanship and provides service and support for 1 year from the date of purchase by the original consumer. Fellowes warrants the cutting blades of the machine to be free from defects in material and workmanship for 1 year from the date of purchase by the original consumer. Flary parts is found to consumer. Fellowes warrants the cutting blades of the machine to be free from defects in material and workmanship for 1 year from the date of purchase by the original consumer. If any part is found to consumer. The super state state is the state of the state of

an reasons of prior me accents, or me accents part ma standard out not pay in close or advance, reanization, at containing and required mishandling, failure to comply with product usage standards, shredder operation using an improper power warranty, please contact us or your dealer. supply (after than listed on the label), or unauthorized repair. Fellowes reserves the right to charge the consumers for any additional costs incurred by Fellowes to provide parts or services outside of the country

## **Factory Service**



#### **Questions or Concerns?**

www.fellowes.com Troubleshooting Registration Manuals	Customer Service & Support Troubleshooting Replacement parts General questions
Canada	+1-800-665-4339
Mexico	+001-800-514-9057
United States	+1-800-955-0959

## Felowes. 1789 Norwood Avenue, Itasca, Illinois 60143-1095 • USA • 630-893-1600

www.fellowes.com

©2015 Fellowes, Inc. Part No. 409344

Please read these instructions before use. Do not discard: keep for future reference.

**Feljowes** Quality Office Products Since 1917

#### **ENGLISH** Model 465M KEY A. SafeSense® Technoloav I. Control Panel and LEDs 1. Overheat (red) B. CD entry C. See safety instructions 2. SafeSense® indicator (vellow) 3. ON/OFF (blue) D. Paper/card entry F Pull-out bin K⊲ 4. Reverse F. Window ⊳ 5. Forward G. Casters H. ON/OFF switch O 1. OFF

2 ON

#### CAPABILITIES

Will shred: Paper, credit cards, CD/DVDs and staples	Maximum:	
Will not shred: Adhesive labels, continous form paper, transparencies, newspaper, cardboard, laminates, paper clips, file folders, X-rays or plastic other than noted above		
Paper shred size: Micro-Cut	Paper entry CD entry wid	
Card/CD shred size:	*8.5 in. x11 other than	
Strip-Cut	EOO choote	

:			
pass	 	 	 
per pass .	 	 	 

ds/CDs per pass	1*
er entry width	
entry width	4-7/8 in. (124mm)

12\*

8.5 in. x11 in., 201b., (75g) paper at 120V, 60 Hz, 5.8Amps; heavier paper, humidity or other than rated voltage may reduce capacity. Maximum recommended daily usage rates: 500 sheets per day; 25 credit cards; 10 CDs. (2) 12 sheets per pass to avoid jams.

Fellowes SafeSense® shredders are designed to be operated in home and office environments ranging between 50 – 80 degrees Fahrenheit (10 – 26 degrees Celsius) and 40 – 80% relative humidity.

### AWARNING: IMPORTANT SAFETY INSTRUCTIONS - Read Before Using

- - Operation, maintenance, and service requirements are covered in the instruction
     manual. Read the entire instruction manual before operating shredders.
     Keep away from children and pels. Keep hands away from paper entry. Always set
  - to off or unplug when not in use. • Keep foreign objects - gloves, jewelry, dothing, hair, etc. - away from shredder
  - openings. If object enters top opening, switch to Reverse (K<I) to back out object.</li>
     Never use aerosol products, petroleum based lubricants or other flammable products on or near shredder. Do not use camed air on shredder.
    - Do not use if damaged or defective. Do not disassemble shredder.
       Do not place near or over heat source or water.
- This shredder has an ON/OFF Switch (H) that must be in the ON (I) position to
  operate shredder. In case of emergency, move switch to OFF (O) position. This
  action will stop shredder immediately.
- Avoid touching exposed cutting blades under shredder head.
- Shredder must be plugged into a properly grounded wall outlet or socket of the voltage and amperage designated on the label. The grounded outlet or socket must be installed near the equipment and easily accessible. Energy converters, transformers, or extension cords should not be used with this product.
- FIRE HAZARD Do NOT shred greeting cards with sound chips or batteries.
   For indoor use only.
- · For macon use only.
- Unplug shredder before cleaning or servicing.

### **BASIC SHREDDING OPERATION**





OFF (0)

## ADVANCED PRODUCT FEATURES

SAFE SENSE/ State chradding immediate

SafeSense® Technology Stops shredding immediately when hands touch the paper opening.

#### SilentShred<sup>™</sup> noise quality shreds without noisy disruptions.

SilentShred<sup>™</sup> Technology

## SAFE SAFESENSE® TECHNOLOGY

Stops shredding immediately when hands touch the paper opening.

## SET-UP AND TESTING



Turn the shredder ON (1) to activate SafeSense® indicator to illuminate

SafeSense® is active and working properly


For more information about all of Fellowes Advanced Product Features go to <u>www.fellowes.com</u>

### PRODUCT MAINTENANCE

## OILING SHREDDER 🕑

All micro-cut shredders require oil for peak performance. If not oiled, a machine may experience diminished sheet capacity, intrusive noise when shredding, and could ultimately stop running. To avoid these problems, we recommend you oil your shredder each time you empty your waste bin.

#### FOLLOW OILING PROCEDURE BELOW AND REPEAT TWICE



\*Apply oil across entry Press and hold forward (▷) 2-3 seconds

**CAUTION** \*Only use a non-aerosol vegetable oil in long nozzle container such as Fellowes 35250

Go to Support Section at <u>www.fellowes.com</u> or see back page of manual for useful telephone numbers.

#### TROUBLESHOOTING

- Overheat Indicator: When the Overheat Indicator is illuminated, the shredder has exceeded its maximum operating temperature and needs to cool down. This
- indicator will remain illuminated and the shredder will not operate for the duration of the recovery time. See Basic Shredding Operation for more information about the continuous operation and recovery time for this shredder.
- SafeSense® Indicator: If hands are too close to the paper entry, the SafeSense® indicator will illuminate and the shredder will stop shredding.

## CLEANING AUTO-START INFRARED SENSORS

Paper detection sensors are designed for maintenance free operation. However, on rare occasions the sensors may become blocked by paper dust causing the motor to run even if there is no paper present. (Note: two paper detection sensors are located in the center of the paper entry).





Dip cotton swab in Using cott rubbing alcohol away any

Using cotton swab, wipe away any contamination from the paper sensors

3

## Turn OFF (O) and Locate Auto-start unplug shredder infared sensor



