

Fujipla ALM 3230 Desktop Automatic Feed Laminator with Integrated Trimmer

Product Spec Sheet



Provided by

MyBinding.com
When Image Matters.

Call Us at 1-800-944-4573

DRYLAM

SELECTION ♦ SOLUTIONS ♦ SIMPLICITY

ALM3230 Automatic Laminator



Labor-free automation with feeding, laminating, and trimming at the touch of a button!

- Heated rollers for crystal clear scratch-free laminations
- Adjustable trim for full encapsulation or precise flush cut
- Sits on a tabletop or optional stand
- Green Button Operation: touch the button and walk away for labor-free, fully trimmed and laminated sheets
- ASAP adhesive laminating films in 1.5, 3, and 5 mil, gloss, matte, and Elegant Silk Matte adheres to hard-to-laminate digitally printed sheets

Eliminate time-consuming, costly hand feeding and trimming in laminating with the new value priced ALM3230 lamination system!

www.drylam.com • P: 888-633-1973 • F: 866-473-0534
23220 W 84th Street • Shawnee, KS 66227

ALM3230 Automatic Laminator

DRYLAM

SELECTION ♦ SOLUTIONS ♦ SIMPLICITY

ALM3230 Automatic Laminator

Key Features:

- Small Foot Print – less than 4 sq. ft.
- Table Top or optional stand with locking roller casters
- 115 Volt, 15 amp service with economy mode
- Ultra quick warm up of less than 5 minutes
- Virtually Unattended Operation
- Digital Sheets sizes: 13"x19", 12"x18", 11"x17", 8.5"x11"
- Laminates copy paper up to 100lb cover stock
- Automatic two side lamination or short one side work
- Adjustable Automatic Flush or Sealed edge trim
- 1 year parts and labor warranty

ALM Exclusive ASAP Roll Film

- Perfect for Digital Print technology
- Anti-static properties

ALM Exclusive ASAP Roll Film

1.5mil, 12.6" x 984 ft
3.0mil, 12.6" x 492 ft
5.0mil, 12.6" x 328 ft
1.2mil, 12.6" x 984 ft, One Side Nylon set (Gloss & Matte Versions)



Model ALM 3230

Laminating Speed
Temperature Range
Ultra Fast Warm-Up Time
Film Thickness
Thickness of Objects
Paper Feeding Capacity
Applicable Sizes:

Fixed speed at 40"/min.
170-270°F
Approximately 5 minutes
1.5, 3, and 5 mil
20lb bond - 100lb cover
100 Sheets, Adjustable Paper Guide

Letter Paper Size 8½" x 11"
Tabloid Paper Size 11" x 17"
Digital Paper Size 12" x 18"
Digital Paper Size 13" x 19"

Trimming Methods
Operation Panel

(2 modes) Flush trim or edge seal for all 4 sides of the print
LCD display for start, stop, temperature, and trim settings, leading and trailing edge side cuts are adjustable

Other Features

Laminated sheet counter, Film tension control, Roller gap lever, Paper thickness feeder adjustment lever

Power Consumption
Power Supply
Net Weight
Optional Accessories

900W
AC 120V (60Hz)
Laminator 100 Lbs. Stand: 48.5 Lbs.
Rolling Stand

www.drylam.com • P: 888-633-1973 • F: 866-473-0534
23220 W 84th Street • Shawnee, KS 66227