



# Gfp

**Graphic Finishing**  
partners

**Where Finishing Comes First.**

## **Gfp 563TH-4RS**

### **ProductionTop Heat Laminator**

What's the best way to make your production even better? Shorten film loading time? Make fewer film changes? Increase throughput speed? The 563TH-4RS does all that and more.

#### **MAXIMIZE PRODUCTIVITY**

*Inline Rotary Slitters*

#### **FAST ROLL CHANGES**

*Front/Rear Swing-out shafts*

#### **EASY LOADING**

*3" Aluminum Quick-Grip shifts*

#### **RUGGED DESIGN**

*Metal Alloy heaters*

#### **VERSATILE**

*Roll-to-Roll operation*



**overlamination • mounting • board pre-coating**

**Spend less time on set-ups and changeovers with swing-out supply shafts.**

50% faster throughput and quick application changes save time, effort and money.



- Swing-out Quick-Grip supply shafts
- Drop-in Quick-Grip rewind shafts
- Photoelectric eye for safety
- Includes rear rewind with Rotary Slitters
- Swing-up feed table & 38" output height
- Metal Alloy heater reduces breakage
- 4.4" diameter rollers
- Roller gap measurement scale

**MyBinding.com**  
When Image Matters.

**mybinding.com**  
**1-800-944-4573**



Includes motorized rear  
rewind with rotary slitters  
for roll-to-roll applications



Media Alignment disks keep  
supply rolls from telescoping

## 563TH-4RS

Rugged Design  
Professional Quality  
Proven Performance  
Economically Priced

### APPLICATIONS

*Signs*  
*Banners*  
*POP Displays*  
*Trade show displays*  
*Graphic mounting*  
*Photo mounting*  
*Dry-erase boards*  
*Floor graphics*  
*Window graphics*  
*Vehicle graphics*

### Warranty:

1 year parts & labor.  
*Installation is available.*

<i>Laminating Width</i>	63"
<i>Roller Diameter</i>	4.5"
<i>Roller Gap</i>	1"
<i>Rear rewind with Slitters</i>	Included
<i>Maximum temperature</i>	140°F
<i>Laminating speed</i>	0-20 ft/min
<i>Pressure adjustment</i>	Hand Wheel
<i>Heat method</i>	Metal Alloy heater
<i>Max. roll diameter</i>	8" OD (top); 16" OD (bottom)
<i>Supply Shafts</i>	2 Swing-out
<i>Tension Adjustment</i>	Single knob
<i>Power Supply</i>	110v 12A
<i>Power Consumption</i>	1320W
<i>Foot Pedal</i>	Included
<i>Stand with casters</i>	Included
<i>Dimensions</i>	87" x 26.5" x 52.5"
<i>Net Weight w/ stand</i>	491 lbs.
<i>Shipping Dimensions (L x W x H)</i>	89" x 35" x 52" 791 lbs.