

PT 331SCC Slit/Cut/Crease/Perf

KEY FEATURES:

Slit, cut, crease or perf in a single pass

150-350 gsm

Interchangeable crease/ perf dies

Full or partial cross perf

Up to 32 creases/ perfs in one pass

Registration mark cut compensation

Preset programs for quick job changeover

Manual cut/crease input for customized jobs

Easily change slitting formats without the need of replacing cartridges



<i>Electrical</i>	110V, 50/60 Hz, 15A	
<i>Paper Weight</i>	150- 350 gsm	
<i>Stock Input Size</i>	Min- 8.2" x 8.2"	Max- 13" x 26"
<i>Finished Output Size</i>	Min- 2" x 1.8"	Max- 13" x 26"
<i>Crease/Perforate</i>	0-32 per pass	
<i>Minimum Gap between Crease</i>	0.1 mm	
<i>Display and Operation</i>	LCD screen and keypad	
<i>Feed</i>	Handfed	
<i>Image shift compensation</i>	Cut compensation (Y axis)	
<i>Gutter Slit</i>	8mm	
<i>Gutter Cut</i>	0mm or 3mm - 15mm	



GRAPHIC WHIZARD AUTHORIZED DEALER:

MyBinding
When Image Matters.

mybinding.com
1-800-944-4573

WWW.GRAPHICWHIZARD.COM

While every effort was made at time of publication to ensure accuracy, Graphic Whizard will not be liable for omissions or errors. Specifications and information are subject to change without notice. Actual results are dependent upon application. Paper stock, print engine used and environmental conditions will affect results.