

# L'Sealer/ Shrink Tunnel Combo

Model:

# PP-1519 ECMC

Economical machine ideal for low to medium production.



**New Design!**  
Featuring  
"Micro Knife"  
Technology



This compact **Model PP-1519 ECMC** L'Sealer with magnetic hold-down and power discharge conveyor with attached Tunnel is only 76" in total length. Featuring new "Micro Knife" technology - will seal PVC or Polyolefin Shrink Films. Tunnel features Live Roller Rod Conveyor with fully Re-Circulating Air Chamber, AC Variable Speed Conveyor, 0-60 FPM, Digital Temperature Control and Automatic Cool Down with Shut Off. A great machine for low to medium production speeds of 8-12 packages per minute. Available in 110 volts or 220 volts.

Model	POWER			Shipping Weight	Seal Dimensions W x L	Tunnel Dimensions L x W x H	Machine Dimensions L x W x H	Max Film Width	Production Rate
	Volts	Phase	Amps						
PP-1519ECMC SERIES	110	1	20	460 lbs.	15 x 19	20 x 16 x 6	76 x 26 x 50	22	8-12 PPM
	220	1	15						

mybinding.com  
1-800-944-4573

**Preferred Pack**<sup>®</sup>  
The New Industry Standard for Quality and Reliability



**Tunnel Control Panel**



\* *Shown with Optional PP 180-24 Gravity Curved Conveyor*

\* *This machine is also available without the Magnet Hold-Down and Power Discharge at a Reduced Price*



**Sealer Control Panel**



**Tunnel Features**

- Fully Re-Circulating Air Chambers
- AC Variable Speed Drive, 0-60 FPM
- Live Roller Rod Conveyor
- Automatic Cool-Down with Shut-Off
- Digital Temperature Control 0° to 400°
- Anti-Jam Safety Feature on Conveyor

**"Micro Knife" Technology**

- Single Piece Teflon Band Ribbon with Round Corner Seal - Reduces Dog Ears
- Will Seal PVC or Polyolefin Shrink Film
- 1 Year Warranty on Band Ribbon
- Dual Magnet Hold Down & Power Discharge Conveyor

**Pin Wheel Hole Punch**

- Easy Load Film Rack
- Multiple Pin Wheels Provide Air Evacuation
- Adjustable Product Loading Tray