Pallet Stretch Wrappers

A low-cost, entry level, semi-automatic machine.

Model:

PP-983 Series



Preferred Pack® The New Industry Standard for Quality and Reliability mybinding.com 1-800-944-4573

Pallet Stretch Wrapper Binding

User-friendly Front Control Panel

•

- PLC Control with 12 Program Memory
- On/Off Switch •
- Top Wrap Count •
- Bottom Wrap Count
- Start/Stop
- Pause Button **Film Tension Control**

Manual/Automatic

- Turntable Speed
- Film Carriage Speed • Emergency Stop Switch

shut off.

Patented triple knurled roller prestretch system with 250% powered pre-stretch. Easy thread design with safety door; if opened machine will



Heavy duty chain drive on turntable with 14 sets of double roller turntable supports. No maintenance or lubrication required.


Technical Specifications:

Production Rate: 30-40 Loads Per Hour Maximum Load: 4,000 lbs.

Power Requirements: 115 Volts, 1 Phase, 15 Amp Maximum Load Size: 50" L x 50" W x 85" H Turntable: 59" diameter - 3/8" Diamond Plate Turntable Drive: 1/2 HP AC variable speed 0-15 rpm Turntable Drive Method: Heavy Duty Chain ANSI #60 Turntable Support: Heavy Duty Delrin Roller Assembly Film Delivery System: Patented triple knurled roller with "Easy Thread Design" to stretch film 250% Machine Dimensions: 108" L x 59" W x 102" H Carriage Elevator: Variable speed 1/2 HP- drive belt Controls: PLC control with 10 program memory Photo Eye:: Will seek height of pallet load Forklift Portable: Yes Home Position: Turntable will automatically return to home position C.E. Approval Exceeds OSHA Safety Standards Warranty: 3 Year Limited Warranty Film Capacity: All Commercial 20" Wide Stretch Film Shipping Weight: 1,500 lbs.

Optional Features:

- 72" diameter turntable
- Tower extension to 105"
- **Base extension**
- Insta-cut automatic film severance
- Weight scale packages



mybinding.com 1-800-944-4573



PP-983 Series