

Model T-275 Automatic Tabletop Bagger

Taking the process a step further, the T-275 Automatic Tabletop Bagger offers increased packaging speed and further automation. The T-275 Automatic Tabletop Bagger automatically and quickly feeds the bag into the loading/sealing position and blows it open making the bag ready to accept the product. After the product is inserted, press the guard-switch or foot-switch to seal the bag and feed another into position.

Digital controls indicate Auto (Paced Rate) or Manual (Foot-switch or Guard-switch) cycle operation, Total Cycle Counter, Seal Time, Fill Time Delay and Seal Point. Set points are saved and automatically recalled when power is shut off.

Standard Features:

- Touch Screen operator panel
- Solid, constant heat seal bar with temperature adjusted through an easy to use temperature controller.
- Patented Teflon Shield™ increases Teflon life tenfold.
- "Guard Switch" Operation - Cycles the machine at the loading area to minimize operator movements, decrease operator fatigue and increase output.
- Foot-switch included
- One year parts warranty
- Patented anti-jamming method detects seal obstructions and reverses seal bar when an obstruction is encountered.
- Universal adjustable funnel included.
- Air knife quickly opens bag with filtered air.
- Adjustable support provided for heavier products.
- Easy threading – pull the bags off the roll and through the pinch rollers with no rollers to thread through.



Specifications

Description

Bag feed method
Seal mechanism
Cycle operation
Bag size range (10" diameter rolls)
Film thickness
Estimated packaging speed
Guard-switch feature
Auto/Paced rate operation
Anti-jam seal bar
Electric
Air
Dimensions
Weight

T-200

Manual registration
Solid heater bar
Semi-automatic
2" x 2" up to 11" x 16"
1 to 5 mil
5 to 15 bags per minute
Standard
Not available
Standard safety feature
110V/60hz (220V/230V, 50/60hz)
.5 cfm/40psi
19-1/2" x 16" x 21-1/2"
50 lbs.

T-275

Automatic registration
Automatic
2" x 2" up to 11" x 16"
1 to 5 mil
10 to 30 bags per minute
Standard
Standard
Standard safety feature
110V/60hz (220V/230V, 50/60hz)
.5 cfm/40psi
19-1/2" x 16" x 21-1/2"
60 lbs.

