

Matrix[®] Omni-Flow is a fully automated deep pile feeder, that is quick & easy to install, set-up and operate.



▲ Matrix Omni-Flow Feeder

KEY FEATURES

- Retrofits to all Matrix Pneumatic & Duplex Systems
- Quick & easy to set-up
- Fully automated lamination & foiling
- Change between paper stock in seconds

GREAT FOR USE IN

- Digital print shops
- Commercial printers
- Copy and print shops
- In-house print

IDEALLY SUITED FOR

- Foiling Prints
- Business cards
- Menus
- Book covers
- Brochures
- Flyers

and many more...

Design

The Matrix Omni-Flow Deep Pile Feeder is a modular system that is designed to be simple to install, set-up and operate. The Feeder can be fitted to all Matrix Pneumatic & Duplex models.

Up to a 100mm/4-inch pile of printed media can be loaded at a time. The Matrix Omni-Flow 330 can also feed in long sheet prints, up to 1250mm/49" in length.

Ideal for both the Digital and Commercial markets for short-to-medium run lamination and foiling of business cards, menus, book covers, greetings cards and bespoke prints.

Specifications

Omni-Flow 330 (SRA3)

| | |
|---|---|
| Max. Mechanical Speed (m/ft/min) | Up to 20m/66' |
| Max. Paper Stack Height (mm/inches) | 100mm/4" |
| Paper Thickness (gsm) | 120-350 |
| Maximum Sheet Width (mm/inches) | 330mm/13" |
| Minimum Sheet Width (mm/inches) | 140mm/5.5" |
| Maximum Sheet Length (mm/inches) | 650mm/25.6" |
| Maximum Sheet Length (mm/inches) (with optional table extension) | 1250mm/49" |
| Compatibility | MX-370P / MX-370DP / MX-530P / MX-530DP |
| Overall Dimensions WxDxH (mm/inches) | 520x950x1100mm/20x37x43" |
| Weight (kg/lbs) | 85.5/188 |
| Power | 165W (220v 50/60Hz) |
| Control Panel | Digital |
| Warranty** | 1 year |

* Maximum speed of Omni-Flow is determined by the maximum speed of the Matrix used

