

### SEAL® 62 PRO D

LAMINATOR WITH PRODUCTIVITY PACK



DUAL HEATED ROLLERS 61 INCH

# INDUSTRIAL PERFORMANCE AT EXCEPTIONAL VALUE







## SEAL® 62 PRO D LAMINATOR WITH PRODUCTIVITY PACK

The SEAL 62 Pro D is a 61" wide mounting laminator and encapsulator offering industrial performance at exceptional value. Productivity pack includes easy-in feed table and slitter to make laminating a snap while the fan banks cools the machine down when both rolls are heated. With fully adjustable dual temperature, speed and pressure settings, and designed on sturdy uni-frame construction, the 62 Pro D is ideal for the more experienced operator. Also includes comprehensive safety system with self checking eyes and emergency stops.

#### **FEATURES:**





#### **Dual Heated Rollers**

Dual heated rollers make most applications, including encapsulation, easy while exceptional roller technology delivers better processing of soft substrates.



#### **Maximum Versatility**

Laminates graphics up to 61" wide at speeds up to 20'/minute. 1 1/2" manual nip adjustment allows for precise operation and accommodates most substrates. The roll-to-roll operation (from bottom unwind) accommodates applications including vehicle wraps. Includes five un-wind/take up shafts and a film saving flip up pull roll system.



#### Easy to Use

Auto-grip upper take-up shaft for winding release liners, stay-put swing-up feed table keeps table up for easier media handling, flip up rollers for no hassle loading, foot switch and ergonomic touch pad control panel. Image guide ensures alignment and roll trough keeps rolled prints in place.

Laminator TypeThermal & Pressure SensitiveMaximum Substrate Length61" (1549 mm)Maximum Laminating Speed20'/min. (6 m/min)Foot SwitchYesFilm TypeThermal & Pressure SensitiveCore Diameter3" (76 mm)Maximum Substrate Thickness (Nip)1½" (38 mm)Maximum Roller Temperature284 °F (140 °C)Roller HeatingDual (Top/Bottom)Temperature ControlYesAuto-Grip Shafts5 (3 Combi/2 Fixed)Maximum Roll DiameterUnwind 12" (305 mm) Release liner upper wind up 6" (152.4 mm) Release liner lower wind up 8" (200 mm)Maximum Roll Weight132.2 lbs. (60 kg)Electric Requirements1N/PE 230VAC +/-10%, 50/60 Hz, 35AMachine Dimensions87.4"H x 56.3"W x 17.7"D (2220mm x 1430mm x 450mm)Machine Weight994 lbs. (450 kg)Shipping Dimensions90"W x 66"H x 38"D (2280mm x 1676mm x 965 mm)Shipping Weight1340 lbs. (608 kg)Warranty2 Year Limited. Extended warranty options available.	nada	
Length  Maximum Laminating Speed  Foot Switch  Yes  Film Type  Thermal & Pressure Sensitive  Core Diameter  3" (76 mm)  Maximum Substrate Thickness (Nip)  Maximum Roller Temperature  Roller Heating  Dual (Top/Bottom)  Temperature Control  Auto-Grip Shafts  5 (3 Combi/2 Fixed)  Maximum Roll  Diameter  Unwind 12" (305 mm) Release liner upper wind up 6" (152.4 mm) Release liner lower wind up 8" (200 mm)  Maximum Roll Weight  132.2 lbs. (60 kg)  Electric Requirements  Machine Dimensions  87.4" H x 56.3"W x 17.7"D (2220mm x 1430mm x 450mm)  Machine Weight  994 lbs. (450 kg)  Shipping Dimensions  90"W x 66"H x 38"D (2280mm x 1676mm x 965 mm)  Shipping Weight  1340 lbs. (608 kg)  Warranty  2 Year Limited. Extended war-	Laminator Type	Thermal & Pressure Sensitive
Foot Switch  Foot Switch  Film Type  Thermal & Pressure Sensitive  Core Diameter  3" (76 mm)  Maximum Substrate Thickness (Nip)  Maximum Roller Temperature  Roller Heating  Dual (Top/Bottom)  Temperature Control  Yes  Auto-Grip Shafts  5 (3 Combi/2 Fixed)  Maximum Roll  Diameter  Unwind 12" (305 mm)  Release liner upper wind up 6" (152.4 mm)  Release liner lower wind up 8" (200 mm)  Maximum Roll Weight  132.2 lbs. (60 kg)  Electric Requirements  Hz, 35A  Machine Dimensions  87.4"H x 56.3"W x 17.7"D (2220mm x 1430mm x 450mm)  Machine Weight  994 lbs. (450 kg)  Shipping Dimensions  90"W x 66"H x 38"D (2280mm x 1676mm x 965 mm)  Shipping Weight  1340 lbs. (608 kg)  Warranty  2 Year Limited. Extended war-		61" (1549 mm)
Film Type  Thermal & Pressure Sensitive  Core Diameter  3" (76 mm)  Maximum Substrate Thickness (Nip)  Maximum Roller Temperature  Roller Heating  Dual (Top/Bottom)  Temperature Control  Yes  Auto-Grip Shafts  5 (3 Combi/2 Fixed)  Maximum Roll  Diameter  Unwind 12" (305 mm)  Release liner upper wind up 6" (152.4 mm)  Release liner lower wind up 8" (200 mm)  Maximum Roll Weight  132.2 lbs. (60 kg)  Electric  Requirements  Hz, 35A  Machine Dimensions  87.4"H x 56.3"W x 17.7"D (2220mm x 1430mm x 450mm)  Machine Weight  994 lbs. (450 kg)  Shipping Dimensions  90"W x 66"H x 38"D (2280mm x 1676mm x 965 mm)  Shipping Weight  1340 lbs. (608 kg)  Warranty  2 Year Limited. Extended war-		20'/min. (6 m/min)
Core Diameter 3" (76 mm)  Maximum Substrate Thickness (Nip)  Maximum Roller 284 °F (140 °C)  Temperature  Roller Heating Dual (Top/Bottom)  Temperature Control Yes  Auto-Grip Shafts 5 (3 Combi/2 Fixed)  Maximum Roll Unwind 12" (305 mm)  Release liner upper wind up 6" (152.4 mm)  Release liner lower wind up 8" (200 mm)  Maximum Roll Weight 132.2 lbs. (60 kg)  Electric 1N/PE 230VAC +/-10%, 50/60  Requirements Hz, 35A  Machine Dimensions 87.4"H x 56.3"W x 17.7"D (2220mm x 1430mm x 450mm)  Machine Weight 994 lbs. (450 kg)  Shipping Dimensions 90"W x 66"H x 38"D (2280mm x 1676mm x 965 mm)  Shipping Weight 1340 lbs. (608 kg)  Warranty 2 Year Limited. Extended war-	Foot Switch	Yes
Maximum Substrate Thickness (Nip)  Maximum Roller Temperature  Roller Heating  Dual (Top/Bottom)  Temperature Control  Yes  Auto-Grip Shafts  5 (3 Combi/2 Fixed)  Maximum Roll  Diameter  Unwind 12" (305 mm)  Release liner upper wind up 6" (152.4 mm)  Release liner lower wind up 8" (200 mm)  Maximum Roll Weight  132.2 lbs. (60 kg)  Electric Requirements  Hz, 35A  Machine Dimensions  87.4"H x 56.3"W x 17.7"D (2220mm x 1430mm x 450mm)  Machine Weight  994 lbs. (450 kg)  Shipping Dimensions  90"W x 66"H x 38"D (2280mm x 1676mm x 965 mm)  Shipping Weight  1340 lbs. (608 kg)  Warranty  2 Year Limited. Extended war-	Film Type	Thermal & Pressure Sensitive
Thickness (Nip)  Maximum Roller Temperature  Roller Heating  Dual (Top/Bottom)  Temperature Control  Yes  Auto-Grip Shafts  5 (3 Combi/2 Fixed)  Maximum Roll  Diameter  Unwind 12" (305 mm) Release liner upper wind up 6" (152.4 mm) Release liner lower wind up 8" (200 mm)  Maximum Roll Weight  132.2 lbs. (60 kg)  Electric Requirements  Hz, 35A  Machine Dimensions  87.4"H x 56.3"W x 17.7"D (2220mm x 1430mm x 450mm)  Machine Weight  994 lbs. (450 kg)  Shipping Dimensions  90"W x 66"H x 38"D (2280mm x 1676mm x 965 mm)  Shipping Weight  1340 lbs. (608 kg)  Warranty  2 Year Limited. Extended war-	Core Diameter	3" (76 mm)
Temperature Roller Heating Dual (Top/Bottom)  Temperature Control Yes  Auto-Grip Shafts 5 (3 Combi/2 Fixed)  Maximum Roll Diameter Unwind 12" (305 mm) Release liner upper wind up 6" (152.4 mm) Release liner lower wind up 8" (200 mm)  Maximum Roll Weight 132.2 lbs. (60 kg)  Electric Requirements Hz, 35A  Machine Dimensions 87.4" H x 56.3"W x 17.7"D (2220mm x 1430mm x 450mm)  Machine Weight 994 lbs. (450 kg)  Shipping Dimensions 90"W x 66"H x 38"D (2280mm x 1676mm x 965 mm)  Shipping Weight 1340 lbs. (608 kg)  Warranty 2 Year Limited. Extended war-		1½" (38 mm)
Temperature Control  Auto-Grip Shafts  5 (3 Combi/2 Fixed)  Maximum Roll  Diameter  Unwind 12" (305 mm)  Release liner upper wind up 6" (152.4 mm)  Release liner lower wind up 8" (200 mm)  Maximum Roll Weight  132.2 lbs. (60 kg)  Electric  Requirements  Hz, 35A  Machine Dimensions  87.4"H x 56.3"W x 17.7"D (2220mm x 1430mm x 450mm)  Machine Weight  994 lbs. (450 kg)  Shipping Dimensions  90"W x 66"H x 38"D (2280mm x 1676mm x 965 mm)  Shipping Weight  1340 lbs. (608 kg)  Warranty  2 Year Limited. Extended war-		284 °F (140 °C)
Auto-Grip Shafts  5 (3 Combi/2 Fixed)  Maximum Roll Diameter  Release liner upper wind up 6" (152.4 mm) Release liner lower wind up 8" (200 mm)  Maximum Roll Weight  132.2 lbs. (60 kg)  Electric Requirements  Hz, 35A  Machine Dimensions  87.4"H x 56.3"W x 17.7"D (2220mm x 1430mm x 450mm)  Machine Weight  994 lbs. (450 kg)  Shipping Dimensions  90"W x 66"H x 38"D (2280mm x 1676mm x 965 mm)  Shipping Weight  1340 lbs. (608 kg)  Warranty  2 Year Limited. Extended war-	Roller Heating	Dual (Top/Bottom)
Maximum Roll         Unwind 12" (305 mm)           Diameter         Release liner upper wind up 6" (152.4 mm)           Release liner lower wind up 8" (200 mm)         Release liner lower wind up 8" (200 mm)           Maximum Roll Weight         132.2 lbs. (60 kg)           Electric         1N/PE 230VAC +/-10%, 50/60 Hz, 35A           Machine Dimensions         87.4" H x 56.3"W x 17.7"D (2220mm x 1430mm x 450mm)           Machine Weight         994 lbs. (450 kg)           Shipping Dimensions         90"W x 66"H x 38"D (2280mm x 1676mm x 965 mm)           Shipping Weight         1340 lbs. (608 kg)           Warranty         2 Year Limited. Extended war-	Temperature Control	Yes
Release liner upper wind up 6" (152.4 mm) Release liner lower wind up 8" (200 mm)  Maximum Roll Weight 132.2 lbs. (60 kg)  Electric 1N/PE 230VAC +/-10%, 50/60 Requirements Hz, 35A  Machine Dimensions 87.4" H x 56.3"W x 17.7"D (2220mm x 1430mm x 450mm)  Machine Weight 994 lbs. (450 kg)  Shipping Dimensions 90"W x 66"H x 38"D (2280mm x 1676mm x 965 mm)  Shipping Weight 1340 lbs. (608 kg)  Warranty 2 Year Limited. Extended war-	Auto-Grip Shafts	5 (3 Combi/2 Fixed)
Electric         1N/PE 230VAC +/-10%, 50/60           Requirements         Hz, 35A           Machine Dimensions         87.4"H x 56.3"W x 17.7"D           (2220mm x 1430mm x 450mm)           Machine Weight         994 lbs. (450 kg)           Shipping Dimensions         90"W x 66"H x 38"D (2280mm x 1676mm x 965 mm)           Shipping Weight         1340 lbs. (608 kg)           Warranty         2 Year Limited. Extended war-		Release liner upper wind up 6" (152.4 mm) Release liner lower wind up 8"
Requirements Hz, 35A  Machine Dimensions 87.4"H x 56.3"W x 17.7"D (2220mm x 1430mm x 450mm)  Machine Weight 994 lbs. (450 kg)  Shipping Dimensions 90"W x 66"H x 38"D (2280mm x 1676mm x 965 mm)  Shipping Weight 1340 lbs. (608 kg)  Warranty 2 Year Limited. Extended war-	Maximum Roll Weight	132.2 lbs. (60 kg)
(2220mm x 1430mm x 450mm)         Machine Weight       994 lbs. (450 kg)         Shipping Dimensions       90"W x 66"H x 38"D (2280mm x 1676mm x 965 mm)         Shipping Weight       1340 lbs. (608 kg)         Warranty       2 Year Limited. Extended war-		•
Shipping Dimensions 90"W x 66"H x 38"D (2280mm x 1676mm x 965 mm)  Shipping Weight 1340 lbs. (608 kg)  Warranty 2 Year Limited. Extended war-	Machine Dimensions	*****
x 1676mm x 965 mm)  Shipping Weight 1340 lbs. (608 kg)  Warranty 2 Year Limited. Extended war-	Machine Weight	994 lbs. (450 kg)
Warranty 2 Year Limited. Extended war-	Shipping Dimensions	· ·
• • •	Shipping Weight	1340 lbs. (608 kg)
	Warranty	

ITEM#	DESCRIPTION
Z64727	SEAL® 62 PRO D LAMINATOR WITH PRODUCTIVITY PACK

