

***4" x 6" 3mil Clear
Vacuum Bags w/ Tear
Notch - 250pcs***

Product Spec Sheet



Provided by

MyBinding.com
When Image Matters.

Call Us at 1-800-944-4573

Product: Vacuum Bags, 3mil (SKU: VB) & Vacuum Tubing, 3mil (SKU: VT)
Description: Clear nominal 3mil Nylon/PE Co-extrusion vacuum barrier film
Application: Cost-effective FDA approved film used extensively for demanding, vacuum applications found in a variety of industries. The films extensibility (ability to stretch) allows it to conform to unique product geometry. Low oxygen transfer rate, high impact resistance and its low cost make it popular with meat, fish, nuts, dried fruit, jerky, and snack products.

TEST ITEM	UNIT	TEST METHOD / CONDITION	TYPICAL VALUE
STANDARD THICKNESS	micron		70μ
TEMPERATURE RANGE	°C / °F		-30°C - 100°C / -22°F - 212°F
OXYGEN PERMEABILITY	cc/m ² /day	ASTM D-3985 (@23°C 75% RH)	61
MOISTURE PERMEABILITY	g/m ² /day	ASTM F-1249 (@40°C X 90% RH)	6.9
TENSILE STRENGTH			
MD	kg/cm ² kg	ASTM 882	370 2.6
TD	kg/cm ² Kg	ASTM 882	360 2.5
ELONGATION			
MD	%	ASTM 882	370
TD	%	ASTM 882	390
TEAR RESISTANCE			
MD	kg/cm Kg	ASTM 882	110 0.8
TD	kg/cm Kg	ASTM 882	110 .8
HEAT SEAL STRENGTH	kg/15mm	YCP TEST METHOD	2.4

This data should be considered as average typical properties and not as a specification. This data is offered for information purposes and does not represent any type of guarantee or warranty of performance. No liability is assumed for any incidents that may arise from use of this data. We urge purchases to conduct independent tests to determine final suitability for their specific application.