SealerSales SPW-982HP High Profile Mid-Range Pallet Stretch Wrapper

Product Spec Sheet



Call Us at 1-800-944-4573



STRETCH PALLET WRAPPER

Model: SPW-982HP | SPW-982LP



Mid-range unit w/ electromechanical brake stretch

- Mechanical break stretch @ 150%
- · 4,000lb load capacity
- · Photo eye seeks pallet load height
- Turntable will automatically return to home position
- "Easy thread design"
- 7" HMI touch screen with programmable memory
- · 110V
- Turntable speed 0-12RPM
- Optional features
 - · 72" diameter turntable
 - Tower extensions to 10%
 - · Base extension to 24"
 - · Load stabilizer top pressure plate
 - Weight scale packages

More Details:

SPW-982HP is a high profile model that can be loaded by forklift only. Ramp not included. SPW-982LP is a low profile model that can be loaded by forklift or pallet jack.

Specifications:

PRODUCTION RATE	30 – 40 LPH	MACHINE DIMENSIONS	108"L X 59"W X 102"H
POWER REQUIREMENTS	110 VOLTS, 1 PHASE, 15 AMP	CARRIAGE ELEVATOR	VARIABLE SPEED ½ HP – DRIVE BELT
MAXIMUM LOAD SIZE	50"L X 50"W x 85"H	CONTROL	PLC CONTROL W/ 12 PROGRAM MEMORY
MAXIMUM LOAD	4,000-LBS	FORK LIFT PORTABLE	YES
TURNTABLE	59" DIAMETER – 3/8" DIAMOND PLATE	CE APPROVAL	EXCEEDS OSHA SAFETY STANDARDS
TURNTABLE DRIVE	½ HP AC VARIABLE SPEED 0-12 RPM	SHIPPING WEIGHT	1,850-LBS
TURNTABLE DRIVE METHOD	HEAVY DUTY CHAIN ANSI #60	FILM CAPACITY	ALL COMMERCIAL 20" WIDE STRETCH FILM
TURNTABLE SUPPORT	HEAVY DUTY DELRIN DOUBLE RING ROLLER ASSEMBLY	SHIPPING DIMENSIONS	124" X 66" X 30"
FILM DELIVERY SYSTEMS	ELECTRO-MECHANICAL BRAKE STRETCH SYSTEM DESIGNED TO PRODUCE FILM YIELDS OF UP TO 150%	WARRANTY	3 YEAR LIMITED WARRANTY

MyBinding.com 5500 NE Moore Court Hillsboro, OR 97124 Toll Free: 1-800-944-4573 Local: 503-640-5920



STRETCH PALLET WRAPPER

Model: SPW-982HP | SPW-982LP



HMI touch screen

PLC control with 12 program memory

On/off switch

Top wrap count (0-12)

Bottom wrap count (0-12)

Start / stop

Manual / automatic

Pause button

Photo eye on/off

Photo eye delay

Film tension control

Turntable speed

•Film carriage speed

Emergency stop switch

Auto tearing



Utilizing 20" machine stretch film, the mechanical brake stretch provides for increased film yields up to 150%



MyBinding.com 5500 NE Moore Court Hillsboro, OR 97124

Toll Free: 1-800-944-4573 Local: 503-640-5920

Heavy duty chain drive on turntable with 18sets of double roller turntable supports.