

From Bindings to Branding -



VersaLam 2700 HC 27"

MARLVE2700

The VersaLam 2700HC 27" Roll Laminator features fully adjustable variable speed and temperature control to accommodate a wide range of films, from 1.5 to 10 mil thick, as well as cold film and mounting boards up to 1/4" thick. It is capable of performing 1- or 2-sided lamination; this versatile machine can handle just about any laminating need, up to 27" wide.



Easy to Use

Adjustable variable speed and temperature controls accommodate 1.5mm - 10mm film, cold film, and mounting boards up to 1/4" thick







— From Bindings to Branding -

VersaLam 2700 HC

27" Hot & Cold Laminator with Stand

Features

- Accommodates up to 10mil film thickness
- Laminates up to 27" in width and mounts up to 1/4"
- Laminates up to 5' per minute
- Allows for one sided and two sided laminating
- Variable speed and temperature controls
- Take up roller for cold lamination
- De-curling bar
- Back pull bar
- On/Off Switch for bottom heat roller
- Max OD for top film 11"
- 5 rear fans w/on and off switch
- Auto shutoff
- Feed tray and front shield sensors
- Rear slitter
- Guide plate for 8.5" x 11"
- Heavy duty all metal construction
- Core size, both 1" and 3"
- Decurling bar included
- Laminator stand included
- UL approved

| Core Size 1" or 3" Max Speed 4 fpm Max Thickness 10 mil Max Width 27" Max Diameter 11" |
|--|
| Max Speed 4 fpm Max Thickness 10 mil Max Width 27" |
| Max Width 27" |
| |
| May Diameter 11" |
| Wax Dialifeter 11 |
| Dimensions 51" x 27" x 24" |
| Electrical Req. 115 V / 60 Hz |

