iTeach® Desktop Sync & Charger



Charge and sync

up to eight devices right on your desktop!



S









- Easily charge and/or sync up to eight USB tablet or phone devices right on your desktop with the compact and attractive iTeach® Desktop Sync & Charger.
- Controlled power management knows which devices need more power, helping to extend battery life
 and saving energy. Includes four charge indicators and on/off power switch.
- Charge or sync up to eight devices with one power cord to the wall. Unit works with most tablets and other devices that are charged via USB.
- USB port in the back of unit is used to sync to a master device, or daisy chain several together using a USB hub.
- Optional syncing mode can be accessed via an iTunes or Windows 7 host computer using the sync USB cable provided.
- Apple devices can be setup and configured using the Apple Configurator available directly from Apple and synced using iTunes. Non-Apple devices will appear as USB drives and can sync via dragging and dropping. Contact your tablet manufacturer to understand the best method of transferring files for your specific device.
- TAA compliant.
- Modified devices, firmware, and custom syncing software may cause compatibility issues with the sync and/or charge capabilities of carts. Please contact us for information regarding the compatibility details of your particular configuration.

Part No.	Item	Product Dimensions	Ship Wt.
27690*	iTeach Desktop Tablet Charger	7"H x 16.5"W x 14"D	15 lbs
27704*	iTeach Desktop Tablet Sync + Charger	7"H x 16.5"W x 14"D	15 lbs

*Ships UPS

Shipping weights are listed on a per item basis and may vary based on quantities ordered. All trademarks and registered trademarks are the property of their respective owners.

A STREET, STRE			
Item	Specification		
Body	Powder-coated steel		
Tablet Compartments	Five (charging) or six (syncing) stage LED light indicators. LED attached/ detached indicator. Slots measure .96"W x 11.14"D.		
Capacity	8 tablets or other mobile computing devices		
Recommended Devices	Versions of the Apple iPad, Apple iPad Mini, Kindle Fire, Barnes & Noble Nook, HP TouchPad, Dell Streak, Samsung Galaxy, Call for assistance with specific device compatibility.		
Input	100-120 VAC at 10 Amps, 50-60 Hz		
Output	8 x 5 VDC at 2.1A		
Profile	Automatic charger emulation profile cycling for USB-IF BC1.2DCP (Android), YD/T-1591 (Apple iPad and iPhone), and RIM (Blackberry) devices. Firmware is upgradeable for future devices. Contact MooreCo for firmware update options.		
Ambient Operating Temperature	32° to 95° F (0° to 35° C)		
Ambient Non-operating Temperature	-4° to 113° F (-20° to 45° C)		
Relative Humidity	5% to 95% non-condensing		
Dimensions	7"H x 16.5"W x 14"D		
Weight	15 lbs		
Exterior	On/Off switch		
Cord	9 ft. power cord		
Warranty	2 year limited on electrical		
Shipping	Ships fully assembled		
LED Indicator	1 red LED: No device charging		
Details	1 blue LED: Device charging for less than 1.5 hours		
	2 blue LEDs: Device charging between 1.5 and 3 hours		
	3 blue LEDs: Device charging between 3 and 4.5 hours		
	4 blue LEDs: Device charging more than 4.5 hours		
	Upper/Lower Blue: Syncing (syncing model only)		



WWW.MYBINDING.COM