

Dry Mount Film


Mounting Adhesive

Dry Mount Film is a 50µ (2 mil) clear PVC mounting film coated on both sides with a heat activated solvent acrylic adhesive, which is protected on both sides by a bleached Kraft grey grid release paper coated on one side with siliconized polyethylene. Available in various sizes.

Typical Applications

- Suitable for mounting to canvas, heavily grained or textured substrates and most other irregular surfaces, including most metals.

Product Structure

Release Liner	1 Side PE Coated Bleached Kraft Grey Grid Paper (Moisture Stable)	
Adhesive	Solvent Acrylic (Heat Activated)	
Carrier	Clear PVC	
Adhesive	Solvent Acrylic (Heat Activated)	
Release Liner	1 Side PE Coated Bleached Kraft Grey Grid Paper (Moisture Stable)	

Physical Characteristics

Film Thickness	50µ (2 mil)
Adhesive Layer	25µ (1 mil) on each side
Ratio Film/Adhesive	1:1
UV Protection Factor	Not Applicable
Outdoor Durability	Not Applicable
Heat Resistance Range	70°C - 95°C (158°F - 203°F)

Process Settings

Equipment Type	Temperature	Dwell Time
Roller Laminator	Not recommended	
Press	85°C to 100°C (185°F to 212°F)	60 to 90 seconds

IMPORTANT NOTE:

Information is intended only as a guide and is given without guarantees. Purchasers should independently determine, prior to use, the suitability of each material for their specific purpose. Follow the indications on the package, ask for the safety data sheets and always follow the indications contained therein.

Only the correct use of the product will allow satisfactory results. For this reason, Drytac is not responsible for improper use of the product, either by application or substrate applied to. Make certain that product is right for the desired use, and work according to the instructions given in our technical data sheets. If in doubt of the appropriate application methods or use, contact Drytac at one of the phone numbers listed below.