

FloBond™

Mounting Adhesive

Flobond™ is a 50µ (2 mil) carrier free “unsupported”, heat reactive, pH neutral mounting adhesive with an activation temperature range of 80°C - 95°C (175°F - 203°F). The bond can be re-activated by re-applying heat.

Typical Applications

- Will bond prints, posters, photographs, fabric, parchment, or foils to a variety of substrates, including mat boards, foam boards and most metals.

Product Structure

Adhesive	None
Carrier	Unsupported 50 micron adhesive
Adhesive	None

Physical Characteristics

Film Thickness	Not Applicable
Adhesive Layer	50µ (2 mil) on each side
Ratio Film/Adhesive	Not Applicable
UV Protection Factor	Not Applicable
Outdoor Durability	Not Applicable
Heat Resistance Range	Not Applicable
Peel Strength (20 min, FTM1)	Not Applicable

Process Settings

Equipment Type	Temperature	Dwell Time
Roller Laminator	Not recommended	
Press	80°C to 95°C (175°F to 203°F)	60 to 90 seconds

IMPORTANT NOTE:

Information is intended only as a guide and is given without guarantees. Purchasers should independently determine, prior to use, the suitability of each material for their specific purpose. Follow the indications on the package, ask for the safety data sheets and always follow the indications contained therein.

Only the correct use of the product will allow satisfactory results. For this reason, Drytac is not responsible for improper use of the product, either by application or substrate applied to. Make certain that product is right for the desired use, and work according to the instructions given in our technical data sheets. If in doubt of the appropriate application methods or use, contact Drytac at one of the phone numbers listed below.