

Drytac FloorTac™ ***Print Media***

Technical Data Sheet



Provided by

MyBinding.com
When Image Matters.

Call Us at 1-800-944-4573

FloorTac[™]

Print Media

FloorTac[™] is a printable polymeric self-adhesive vinyl specifically designed for floor graphics. It is available in 3.5 mil matte white with removable acrylic adhesive, 3.5 mil matte white with removable gray solvent acrylic adhesive, and 3.5 mil gloss clear with removable acrylic adhesive.

Typical Applications

- Ideal for short-term indoor advertising where floor graphics are applied to floor tiles, sealed wood, sealed concrete, waxed vinyl, marble, terrazzo, or ceramic tiles.
- Should be used with Drytac's Emerytex laminating film for an approved slip resistant finish.
- For best results, leave a ¼" non-printed border around the edge of the image.

Recommended Printer Platforms

- Solvent
- Eco Solvent
- Latex
- UV

Physical Characteristics

Thickness	3.5 mil	3.5 mil	3.5 mil
Adhesive	1 mil removable aqueous acrylic adhesive	1 mil removable gray solvent acrylic adhesive	1 mil removable aqueous acrylic adhesive
Finish and Color	Matte White	Matte White	Gloss Clear
Release Liner	90 # Poly Coated Kraft	90 # Poly Coated Kraft	90 # Poly Coated Kraft

Options for Your Application Needs

FloorTac[™] comes in several versions to best suit your needs. The gray backed adhesive version should be used for more demanding applications. The clear version provides a frosty appearance to the parts of the graphic without ink.

Installation Recommendations

Please see FloorTac[™] installation instructions for further details. The surface must be clean and smooth and free of defects before application.

IMPORTANT NOTE:

Drytac is not responsible for improper use of the product. Make certain that product is right for the desired use, and work according to the instructions given in our technical data sheets. If in doubt of the appropriate application methods or use, contact Drytac at one of the phone numbers listed below.