

GBC 640T Wide Format Roll Laminator - 1880009

Product Spec Sheet



Provided by

MyBinding.com
When Image Matters.

Call Us at 1-800-944-4573



640t Wide Format Roll Laminator

Does the job others can't

Introducing the all new GBC® 640t wide format roll laminator. This production quality wide format roll laminator system runs cold finishing jobs roll to roll up to 16 feet per minute for increased productivity and superior output.



Features and benefits

Improved productivity

- Run roll to roll applications at up to 16 fpm for improved productivity and profits

Easy to use

- Simple push button with LCD display control panel takes the guesswork out of pressure and temperature settings
- Foot pedal for hands free operation
- Film shafts swing out for easy loading and unloading
- Front table is easily adjusted or removed for easy access to rollers
- Unique pressure plate holds prints in place
- High release silicone rollers allow for easy cleaning

Versatile

- Laminate and mount graphics up to 61" in width
- Mechanical roller adjustment, heat rollers gap to a maximum 1/2" for mounting applications

Superior output

- Top roller heat assist designed for improved adhesion, reduces silvering and faster curing times
- Intelligent controller monitors and maintains consistent temperature for optimum quality

Safety first

- A disruption of the photo beam stops the rollers to protect fingers from getting caught
- An emergency stop button is conveniently located to quickly stop the laminator and provide maximum operator control

Warranty

- The GBC 640t wide format laminator includes 1 year onsite service coverage

Films

For best results use high-quality GBC films

- Arctic® Pressure Sensitive
- Arctic® Mounting Adhesives

Applications

- Trade show graphics
- Vehicle graphics
- Pop displays
- Floor graphics
- Flexible & rigid displays
- Posters & banners
- Backlit displays

Machine specifications

| | |
|-----------------------------|--------------------------------------------------------------------------------------|
| 4 Film shafts | 2 unwinds, 2 rewinds |
| Maximum film width | Up to 61" |
| Maximum film thickness | Up to 10 MIL |
| Maximum roll diameter | Up to 5" PSA film on a 3" core |
| Maximum mounting capability | 1/16" To 1/2" |
| Speed | 3 To 16 feet per minute in forward position 3 Feet per minute in reverse position |
| Temperature | Up to 140 degrees fahrenheit |
| Machine dimensions | 78.0" W x 48.0" H x 30.0" D |
| Weight | Net wt. – 350 lbs. Shipping wt. – 410 lbs |
| Power requirements | 220 V, 9.0 A, 2,000 W, 60Hz |
| Plug configuration | NEMA 6 – 15P |
| Safety | c/UL listed |

Onsite Operator and Process Training

New Onsite Operator and Process Training is currently available for the GBC 640t wide format roll laminator. Hands-on training with your equipment, in your facility, working with your applications by a qualified GBC training professional. Call 800.723.4000 or go online at www.gbconnect.com for more information.

