


# Interlam™ Pro Leather UV (175μ/7 mil) Overlaminating Film

Interlam™ Pro Leather UV is a UV stabilized, clear PVC overlaminating film with a leather emboss textured finish, coated on one side with a pressure sensitive, aqueous acrylic adhesive that is protected by a plain bleached Kraft release paper, polyethylene coated and siliconized on one side. Available in various sizes.

### Typical Applications

- Recommended for book and album covers, framed mats, photos, and graphic prints.
- Provides UV protection for outdoor graphics.

### Product Structure

Film	Leather PVC	
Adhesive	Aqueous Acrylic (Pressure Sensitive)	
Release Liner	1 Side PE Coated Siliconized Plain Bleached Kraft Paper	

### Physical Characteristics

Film Thickness	150μ (6 mil)
Adhesive Layer	25μ (1 mil)
Ratio Film/Adhesive	6:1
UV Protection Factor	Film contains UV stabilizers, which prevent film degradation and provide UV protection to the underlying image
Outdoor Durability	12 months without discernable change
Heat Resistance Range	70°C - 95°C (158°F - 203°F)
Peel Strength (20 min, FTM1)	23 N/25mm

### Process Settings

Equipment Type	Temperature	Speed
Roller Laminator	Room temperature to 49°C (120°F)	0.3m to 1.75m (1 ft to 6 ft) per minute
Press	<b>Not recommended</b>	

### IMPORTANT NOTE:

Information is intended only as a guide and is given without guarantees. Purchasers should independently determine, prior to use, the suitability of each material for their specific purpose. Follow the indications on the package, ask for the safety data sheets and always follow the indications contained therein.

Only the correct use of the product will allow satisfactory results. For this reason, Drytac is not responsible for improper use of the product, either by application or substrate applied to. Make certain that product is right for the desired use, and work according to the instructions given in our technical data sheets. If in doubt of the appropriate application methods or use, contact Drytac at one of the phone numbers listed below.