

MBM 352F Tabletop Friction Paper Folding Machine

Instruction Manual



Provided by

MyBinding.com


When Image Matters.

Call Us at 1-800-944-4573

→ 352F PROFESSIONAL SERIES TABLETOP FOLDER

dual roller friction feed system accepts a wide variety of stocks, including carbonless sheets | adjusts in seconds for standard and custom folds | variable speed control | powered exit conveyor | sheet separation from top of fanned stack | polyurethane foam rollers eliminate the need for fold roller pressure settings | heavy-duty, non-flexing side frames | needle bearings for high speed production | optional extended delivery system, crossfold for right-angle folding, and slitting, scoring, and perforating attachments

Dimensions (D x W x H): 22 ¼ x 41 ¾ x 14 ½ inches, Shipping weight: 105 lbs.



DUAL FEED ROLLERS



The dual roller feed system folds a wide range of stock.

POWERED CONVEYOR



A powered exit conveyor ensures smooth ejection of folded paper.

→ 352F

Speed	22,000 sheets/hr*
Paper size	2" x 2 ¼" to 14" x 21 ¼"
Paper weight	13 to 110 lbs.*
Sheet capacity	300*
Power supply	115 V, 60 Hz

* may vary due to variations in paper and power supply

Dealer:

MBM
CORPORATION

3134 Industry Drive
North Charleston, South Carolina 29418
800-223-2508, fax: 843-552-2974
www.mbmcorp.com

IDEAL.MBM
CORPORATION

1675 Sismet Road, unit 4
Mississauga, Ontario L4W 4K8
800-387-2528, fax: 905-840-1114
www.ideal-mbm.com



All technical data is approximate and subject to change. © MBM Corporation, 2/2010.
When Image Matters.