GBC Octiva Heat Activated Films

Product Spec Sheet



Call Us at 1-800-944-4573



Product Specification Sheet



Heat-Activated Films

Octiva thermal films contain an increased polyester content that provides excellent protection, as well as high clarity and rigidity for overlamination or encapsulation of digital color images.

Octiva Gloss

Available in 1.7, 3, 5, & 10-mil

High gloss polyester films are perfect for store displays or promotional signage where indirect lighting will prevail.

Octiva Lustre

Available in 3-mil

A semi-gloss (satin finish) film using a filled polyester substrate. Applications include point-of-purchase displays, indoor signage or brightly lit areas. Octiva Lustre is the most color-correct film on the market.

Octiva Matte

Available in 3-mil

A matte finish offers a crystal-sharp image with virtually no reflection when used on products displayed in direct light. Excellent for trade show displays, window signs, and more.

Octiva Matte Hardcoat

Available in 5-mil

Hard coated matte polyester substrate with scuff resistant properties. Used where there is a high degree of wear. Matte finish diminishes reflection from direct lighting applications.

Octiva Write Erase

Available in 1.7-mil

A gloss film designed to be written on with dry erase markers and wiped clean. Applications include teaching aids, presentations, schedules, meetings, litigation graphics, etc.

Octiva Films

Octiva Film	Mil Thick	Film/ Adhesive Ratio	Recommended Speed	Core Size
Gloss	1.7	.5/1.2	3-6 fpm	3"
	3	.6/2.4	3-6 fpm	3"
	5	3/2	3-6 fpm	3"
	10	7/3	3-6 fpm	3"
Lustre	3	.5/2.5	3-6 fpm	3"
Matte	3	.5/2.5	3-6 fpm	3"
Matte Hardcoat	5	3/2	3-6 fpm	3"
Write Erase	1.7	.5/1.2	3-6 fpm	3"

Description

Polyester substrate coated with a copolymer adhesive.

Characteristics

High clarity and rigidity of digital color imaging.

Temperature

220°-250°F

3" Core

Core
3 mil Octiva Lustre
302330525" x 250'
302335438" x 250'
302334538" x 500'
302331543" x 500'
302330851" x 250'
302331651" x 500'
302332055" x 250'
302332255" x 500'
301273461" x 500'
7 mil Oation Matte
3 mil Octiva Matte 301782938" x 250
302255638" x 500' 302250743" x 250'
302253743" x 500
302250651" x 250
302253851" x 500
302251355" x 250
302254055" x 500
302234035 X 300
5 mil Octiva Matte Hardcoa
312371738" x 250'
312370443" x 250'
312370551" x 250'
312370655" x 250'
1.7 mil Octiva Write Erase
302135738" x 250
302702351" x 250

LIMITED 12-MONTH WARRANTY

GBC warrants to the original purchaser for a period of 12 months after purchase that this laminate when applied using GBC-recommended materials and equipment and in accordance with GBC's written instructions will be free from defects in workmanship and material under normal use. GBC's obligation under this warranty is imited to replacement of any laminate found to be defective by GBC. This warranty is in lieu of all other warranties expressed or implied. WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED. Any representations or promises inconsistent with, or in addition to, this warranty are unauthorized and shall not be binding upon GBC. In no event shall GBC be liable for any special, incidental or consequential damages, whether or not foreseeable. This warranty shall be void if the laminate has been misused; mishandled; damaged by negligence, by accident, during shipment, or due to exposure to weather or extreme conditions; applied not using GBC-recommended materials and equipment; or applied not in accordance with GBC's written instructions.