

### RemoTac<sup>™</sup>

### Mounting Adhesive

RemoTac<sup>™</sup> is a 12µ (0.5 mil) clear polyester mounting film coated on one side with a pressure sensitive, removable solvent acrylic adhesive, which is protected by a bleached Kraft release paper coated on both sides with siliconized polyethylene. The other side of the mounting film is coated with a pressure sensitive, permanent aqueous acrylic adhesive, which is exposed and self-wound onto the roll. Available in various sizes.

#### Typical Applications

- Ideal for interchangeable signs and graphics for countertops, presentation graphics and retail display boards.
- Removes well from a variety of substrates such as glass, painted metal and aluminium.
- High tack makes RemoTac<sup>™</sup> an aggressive removable mounting film for difficult, low energy surfaces.
- Suitable for both indoor and short-term outdoor use.

#### Product Structure

Adhesive Layer	Permanent Aqueous Acrylic (Pressure Sensitive)	62µ (2.5 mil)
Film	Clear Polyester	
Adhesive	Removable Solvent Acrylic (Pressure Sensitive)	
Release Liner	2 Side PE Coated, 2 Side Siliconized Kraft Paper	

#### Physical Characteristics

Film Thickness	12µ (0.5 mil)
Adhesive Layer	25µ (1 mil) on each side of the film
Ratio Film/Adhesive	0.25:1
UV Protection Factor	Not Applicable
Outdoor Durability	Up to 3 months
Heat Resistance Range	Up to 49°C (120°F)
Peel Strength (20 min, FTM1)	12 N/25mm - Permanent 7.5 N/25mm - Removable

#### Process Settings

Equipment Type	Temperature	Speed
Roller Laminator	Room temperature to 49°C (120°F)	0.3m to 2.5m (1 ft to 8 ft) per minute
Press	Not recommended	

#### IMPORTANT NOTE:

Information is intended only as a guide and is given without guarantees. Purchasers should independently determine, prior to use, the suitability of each material for their specific purpose. Follow the indications on the package, ask for the safety data sheets and always follow the indications contained therein.

Only the correct use of the product will allow satisfactory results. For this reason, Drytac is not responsible for improper use of the product, either by application or substrate applied to. Make certain that product is right for the desired use, and work according to the instructions given in our technical data sheets. If in doubt of the appropriate application methods or use, contact Drytac at one of the phone numbers listed below.