Standard PC-P430 Electric 17" Desktop Paper Cutter





PC-P430

Paper Cutter

Table-top Paper Cutter for office efficiency and cost savings.



Features

- 1. Maximum cut width is 434 mm / 17", maximum thickness is up to 23 mm / 0.9".
- 2. Minimum cut length is 50 mm / 1.97" for small format applications such as business cards.
- 3. Sheets are trimmed by simply setting the sheets and pressing the dual push buttons. An automatic clamping press for easy operation.
- 4. Illuminated cut line conveniently identifies the cut position for easy, accurate cutting.
- 5. Innovative cutting knife design for easy and safe knife replacement.



The perfect office cutter for cutting for cutting of printed sheets or trimming books.



Dual Push Buttons

The PC-P430 is activated only when the safety cover is closed and both cutting buttons are



simultaneously pressed. The two buttons are sufficiently spaced to ensure operator safety.

Safety Full Cover

The front cover will not open during the operation. The full cover keeps your fingers away from the moving part.

Safety Power Key

Spare Knife with Sheath

Cut Stick

The power switch can be key activated to limit user access.

PC-P430 Option Pedestal with Wheels: MT-P43 Maintenance Kit Quantity

2 pcs

Push-out Lever

The operator simply pushes a lever to move cut sheets forward for easy removal.



5 Cut Stick Lift Lever

The cut stick is easily replaced by using the integrated lift lever.



6 Cutting Line

Illuminated cut line conveniently identifies the cut position for easy sheet positioning.

Backgauge Handle

Backgauge position can be adjusted by turning the handle.

Backgauge Free Mechanism

Sheets longer than 320 mm / 12.5" can be trimmed using the backgauge free mechanism.



Cutting Knife Counter

Cut cycles are indicated on a digital counter to help determine when the cutting knife should be replaced.

10 Press Section

The sheets are pressed and cut automatically by pressing the cutting buttons. A special cutout is provided to prevent book spines from crushing.

Double Lead Screw System

Accurate backgauge raceway keeps the gauge square to ensure accurate cutting.



| PC-P430 Specifications | | |
|------------------------|--|---|
| Cutting Width | | Max. 434 mm / 17.08" |
| Cutting Height | | Max. 23 mm / 0.9" |
| Cutting Depth | | Max. 320 mm / 12.59" Min. 50mm / 1.97" |
| Clamp System | Spring-Operated | |
| Push-out Length | Max. 25 mm / 0.98" | |
| Cutting Speed | About 4 seconds per cycle (100 V, 60 Hz) About 4.8 seconds per cycle (100 V, 50 Hz) | |
| Voltage/Frequency | Single Phase 110 to 120 V, 60 Hz Single Phase 220 to 240 V, 50 / 60 Hz | |
| Rated Current | Single Phase 110 to 120 V, 60 Hz, 3.9 A Single Phase 220 to 240 V, 50 Hz, 1.6 A | |
| Machine Dimensions | W675 x D600 x H375 mm / W26.6" x D23.7" x H14.8" | |
| Machine Weight | 66 kg / 145.4 lb | |

MyBinding.com 5500 NE Moore Court Hillsboro, OR 97124 Toll Free: 1-800-944-4573

Local: 503-640-5920

^{*}The machine design and specifications are subject to change without any notice.